

TECHNICAL DATASHEET OLYTECH MONDIAL

“755L”“755XL”“755SP”



OLYTECH
mondial BRUSHLESS 12V



Davide e Luigi Volpi S.p.A.
Via San Rocco, 10
46040 CASALROMANO MN –ITALIA

COMPANY WITH QUALITY SYSTEM
MANAGEMENT CERTIFIED BY ICIM
= ISO 9001 =

Olytech MONDIAL is the electric harvester with two arms for tine's fixing with oscillatory movement allows a high performance of harvesting-patented. Design with tilting head for the optimal access into the trees, studied for the quick substitution of the tines.

Equipe with telescopic extension or fix pole and ergonomic handle.

Olytech MONDIAL works with a brushless electric motor 12 V directly powered by the battery and equipped with electronic board into the handle.

Adjustable speed on 3 levels.

Available in 3 versions: 755L extendable from 2100 mm to 3000 mm, 755XL extensible from 2400 mm to 3600 mm and 755SP with fix pole.

Olytech MONDIAL allows a productivity of 90/130 Kg/hour.

HARVESTER OLYTECH 755L – 755XL – 755SP	
TYPE OF MOVEMENT	two arms for tine's fixing with oscillatory movement allows a high performance of harvesting-patented.
ELEMENTS OF THE HEAD	4+4 TINES IN CARBON FIBER – QUICK SUBSTITUTION
MOTOR	BRUSHLESS12V cc AD high performance and low electric consumption
POWER SUPPLY	ELECTRIC 12V
RECOMMENDED BATTERY	12 V cc – 70-80 Ah
MOTOR PROTECTION	ELECTRONIC
LENGHT	FROM 2100 mm TO 3000 mm 455L FROM 2400 mm TO 3600 mm 455XL 2440 mm 455SP
TOTAL WEIGHT OF THE TOOL	755L = 2,4 Kg – 755XL = 2,7 Kg – 755SP = 2,0 Kg
PRODUCTIVITY	90÷130 kg/ora
SPEED	REGOLABILE 850RPM – 950RPM – 1050 RPM
SUPPLY CABLE	15 m WITH CLAMPS AND CONNECTOR
HANDLE	ERGONOMIC WITH ON/OFF SWITCH, SPEED CONTROL AND RESISTANT CABLE

IMPORTANT: FOLLOW STRICTLY THE INSTRUCTIONS RELATED TO THE USE OF THE PRODUCTS, GIVEN ON THE INSTRUCTION MANUAL.