



Iso 9001 Cert. N. 5600/0

Tel. 0376 76012 – 76009

Fax 0376 76408

E-Mail: info@volpioriginale.it

<http://www.volpioriginale.it>

Davide e Luigi Volpi S.p.A.

Via San Rocco, 10

46040 CASALROMANO MN -ITALIA

Cap. Soc. € 504.000,00 i.v.

R.E.A. 75331 MANTOVA

N. POSIZIONE: MN003037

TRIB. MANTOVA REG.IMP.2586

C.F. E P.IVA 00136560208

VAT.IT00136560208

TECHNICAL DATA SHEET - MANUAL SPRAYER VT10E

The sprayer Volpitech VT10 with EPDM gaskets is designed for dispensing liquid solutions.

Sprayer	With safety valve
Lance lenght	40 cm
Max Pression	3 bar
Tank material	Polyethylene
Spring and Pin material	Inox aisi 304
Handle and Valve material	Inox aisi 302
O-rings material	EPDM
Tank capacity	10 Lt.
Filler opening diameter	60 mm
Nozzle material	Polypropylene
Total Net Weight	2,470 gr.
Package dimensions	22x22x65 cm.

Nozzle performance:

PRESSION BAR	FLOW LT/MIN	NOZZLE (HOLE 1,25)
1,0	0,22	60° ROSE
1,5	0,29	
2,0	0,37	
1,0	0,46	JET
1,5	0,61	
2,0	0,77	

The sprayer resists to low solutions (up to about 20%) of alkaline components, detergents, industrial disinfectants, 10% ammonia, 5% bleach.

The sprayer is not resistant to solvents, trichlorethylene, lacquers, petrol, diesel, hydraulic oils and fuels.

The sprayer has to be washed after each use and run with clean water for a few minutes.

IMPORTANT: PLEASE CAREFULLY FOLLOW THE USE AND MAINTENANCE INDICATIONS REPORTED ON THE USER MANUAL.