



Iso 9001 Cert. N. 5600/0

Tel. 0376 76012 – 76009

Fax 0376 76408

E-Mail: info@volpioriginale.it

<http://www.volpioriginale.it>

Davide e Luigi Volpi S.p.A.

Via San Rocco, 10

46040 CASALROMANO MN -ITALIA

Cap. Soc. € 504.000,00 i.v.

R.E.A. 75331 MANTOVA

N. POSIZIONE: MN003037

TRIB. MANTOVA REG.IMP.2586

C.F. E P.IVA 00136560208

VAT.IT00136560208

TECHNICAL DETAILS FOR COMPRESSION SPRAYER VT2E

VOLPITECH2 EPDM has been created to spray liquid solutions:

Compression sprayer	With discharge valve and adjustable plastic nozzle
Pression bar	2
Material of the head	Polypropylene
Material of the tank	High Density Polyethylene
Material of the closing pin	Special plastic
Pin's and valve's springs material	Stainless steel AISI 302
Material of the nozzle	Polypropylene
Material O-ring	EPDM
Capacity of the tank Lt.	2
Diameter mouth of filling	60
Nozzle	Adjustable
Net weight of the sprayer gr.	460
Dimension of the packaging	48x37x31
Weight of the packaging for 10 pcs. kg	5

Nozzle performance:

PRESSION BAR	CAPACITY LT/MIN	SPRAYER VT2 (HOLE1,25)
1,0	0,22	ROSE A 60°
1,5	0,29	
2,0	0,37	
1,0	0,46	FAN NOZZLE
1,5	0,61	
2,0	0,77	

The sprayer resists to low solutions (until around 20%) of alkaline components, detergents, industrial sanitizers.

The sprayers do not resist to acetone, solvents, varnish.

The sprayer has always to be washed after every usage.