

## TECHNICAL DATASHEET ELECTRIC PUMP

### VT7





Davide e Luigi Volpi S.p.A.  
Via San Rocco, 10  
46040 CASALROMANO MN –ITALIA

COMPANY WITH QUALITY SYSTEM  
MANAGEMENT CERTIFIED BY ICIM  
= ISO 9001 =

Tank capacity	7 Lt
Tank material	Polypropylene
Operating pressure	2,0 bar
Safety valve	Standard - 3 bar calibration
Pump	Diaphragm
Pressure switch	Standard for max pressure control
Rechargeable lithium battery	7,4 Vdc 2,6 Ah 19,24 Wh
Charging socket	Micro USB
Battery charge time	Up to 2,5 hours
Spraying Liters for each battery charge	Up to 45 liters
Extension	Nylon
Handles	Lever Jet
Nozzle	Polypropylene
Shoulder strap	Adjustable
Gaskets	FPM
Delivery hose length	1,2 mt
Filling mouth diameter	60 mm
Temperature min. / max.	5° C / 40° C
Overall dimensions	230 x 215 x 460
Empty pump weight	1,35 Kg

This pump resists to low solutions (up to about 20%) of hydrochloric acid, diesel oil, caustic soda, bleach, detergents, herbicides, degreasers, industrial disinfectants, descalers, hydraulic and fuel oils, ethyl alcohol.

**The pump must be cleaned after every use.**

BAR PRESSION	CAPACITY LT/MIN	ADJUSTABLE NOZZLE BORE Ø 1,25 mm
1,0	0,22	60° ROSE
1,5	0,29	
2,0	0,37	
1,0	0,46	JET
1,5	0,61	
2,0	0,77	

**IMPORTANT: PLEASE CAREFULLY FOLLOW THE INSTRUCTIONS WRITTEN IN THE OWNER'S MANUAL.**