
TECHNICAL DATASHEET WHEELBARROW SPRAYER
“744MOC”



The wheelbarrow sprayer is ideal for spraying liquids at high pressure, it consists of a painted steel frame with 2 rubber wheels that allow an easy displacement, a 120 Lt polyethylene tank, an engine 1.5 HP - 230V single-phase electric pump, a 25 bar max. pressure AR252 diaphragm pump, a metal hose reel, 50 mt high pressure hose and a metal lever lance 65cm.



Davide e Luigi Volpi S.p.A.
Via San Rocco, 10
46040 CASALROMANO MN –ITALIA

COMPANY WITH QUALITY SYSTEM
MANAGEMENT CERTIFIED BY ICIM
= ISO 9001 =

2 WHEELS WHEELBARROW	
TANK MATERIAL	POLYETHYLENE
TANK CAPACITY	120 Lt
FRAME	PAINTED STEEL WITH 2 WHEELS
DIMENSIONS	108 x 71 x 95
WEIGHT	22 Kg
SINGLE-PHASE ELECTRIC MOTOR	
TYPE	SINGLE-PHASE ELECTRIC
ENGINE CAPACITY	212 cc
COOL DOWN	AIR CUSHION
POWER	1,5 HP – 230V
WEIGHT	11 Kg
DIAPHRAGM PUMP AR252	
MAX RPM	650 g/min.
MAX CAPACITY	25 L/min.
MAX PRESSURE	25 bar
WORKING TEMPERATURE	5°C ÷ 40°C
LUBRICATING OIL	CD 15W-40
WEIGHT	8,8 Kg
HIGH PRESSURE LEVER LANCE	
MATERIAL	INOX STEEL – BRASS
MAX PRESSURE	15÷40 bar
NOZZLE DIAMETER	1,5 mm
LENGHT	65 cm
WEIGHT	0,6 Kg

IMPORTANT NOTE: PLEASE CAREFULLY FOLLOW THE USE AND MAINTENANCE INDICATIONS REPORTED ON THE USER MANUAL.