
TECHNICAL DATASHEET WHEELBARROW SPRAYER
"744VIC"



The wheelbarrow sprayer is ideal for spraying liquids at high pressure, it consists of a painted steel frame with 2 rubber wheels that allow an easy displacement, a 120 Lt polyethylene tank, a combustion engine RATO R210- 4 stroke 5HP, a diaphragm pump AR252 max. pressure 25 bar, a metal hose reel, 50 mt high pressure hose and a metal lever lance 65cm.



Davide e Luigi Volpi S.p.A.
Via San Rocco, 10
46040 CASALROMANO MN –ITALIA

COMPANY WITH QUALITY SYSTEM
MANAGEMENT CERTIFIED BY ICIM
= ISO 9001 =

TWO WHEELS WHEELBARROW	
TANK MATERIAL	POLYETHYLENE
TANK CAPACITY	120 Lt
FRAME	PAINTED STEEL WITH 2 WHEELS
DIMENSIONS	108 x 71 x 95
WEIGHT	22 Kg
RATO MOTOR R210	
TYPE	SINGLE CYLINDER, 4 STROKE
ENGINE CAPACITY	212 cc
COOL DOWN	AIR CUSHION
POWER	5 HP
POWER SUPPLY	PETROL
DIMENSIONS	390 x 320 x 345
WEIGHT	16 Kg
DIAPHRAGM PUMP AR252	
MAX RPM	650 g/min.
MAX CAPACITY	25 L/min.
MAX PRESSURE	25 bar
WORKING TEMPERATURE	5°C ÷ 40°C
LUBRICATING OIL	CD 15W-40
WEIGHT	8,8 Kg
HIGH PRESSURE LEVER LANCE	
MATERIAL	INOX STEEL – BRASS
MAX PRESSURE	15÷40 bar
NOZZLE DIAMETER	1,5 mm
LENGHT	65 cm
WEIGHT	0,6 Kg

**IMPORTANT NOTE: PLEASE CAREFULLY FOLLOW THE USE AND
MAINTENANCE INDICATIONS REPORTED ON THE USER MANUAL.**