

TECHNICAL DATASHEET
KNAPSACK SPRAYER "RECORD" WITH PLASTIC PUMP
COD. 95PUG/95PSF



The Model "Record" has been designed for the distribution of liquid solutions.

Mod. Record 95PUG/95PSF	With hydraulic agitator
Working pressure	6 bar
Tank material	Polyethylene HD
Tank capacity	Lt. 20
Hose length	Mt. 1,50
Filling entrance diameter	mm. 115
Pump	Plastic Ø52 mm
Nozzle	Mod. Get 928
Net weight Kg	3,950
Packing dimensions cm	45x24x61



Davide e Luigi Volpi S.p.A.
Via San Rocco, 10
46040 CASALROMANO MN –ITALIA

COMPANY WITH QUALITY SYSTEM
MANAGEMENT CERTIFIED BY ICIM
= ISO 9001 =

Spraying performance:

PRESSURE BAR	FLOW RATE LT/MIN	NOZZLE (HOLE 1,5)
1,7 2,3 2,9	0,77 0,93 1,10	60°
1,7 2,3 2,9	1,18 1,39 1,54	JET

CLEANING: wash the tank after every use with clean water.

IMPORTANT: CAREFULLY FOLLOW THE INDICATIONS FOR USE REPORTED INTO THE USER'S MANUAL.