

TECHNICAL DATASHEET
KNAPSACK SPRAYER "RECORD" 20lt WITH BRASS PUMP
COD. 95UG/95SF



The model "Record" has been designed for the distribution of liquid solutions.

Mod. Record 95UG/95SF	With floating OR and hydraulic agitator
Working pressure	6 bar
Tank material	Polyethylene
Tank capacity	Lt. 20
Hose length	Mt. 1,50
Filling diameter	mm. 115
Pump	Brass Ø44 mm
Nozzle	Get 928
Net weight Kg	4,45
Packing dimensions cm	45x24x61



Davide e Luigi Volpi S.p.A.
Via San Rocco, 10
46040 CASALROMANO MN –ITALIA

COMPANY WITH QUALITY SYSTEM
MANAGEMENT CERTIFIED BY ICIM
= ISO 9001 =

Spraying performance:

PRESSURE BAR	FLOW RATE LT/MIN	NOZZLE (HOLE 1,5)
1,7	0,77	60°
2,3	0,93	
2,9	1,10	
1,7	1,18	JET
2,3	1,39	
2,9	1,54	

CLEANING: wash the tank after every use with clean water.

IMPORTANT: CAREFULLY FOLLOW THE INDICATIONS FOR USE REPORTED INTO THE USER'S MANUAL.