

TECHNICAL DATASHEET
KNAPSACK SPRAYER "UNI" 12/15Lt WITH BRASS PUMP
COD. 81UG/78UG



UNI knapsack sprayer is manufactured for the distribution of liquid solutions.

Sprayer UNI 81UG-81SF 78UG-78SF	With floating OR and hydraulic agitator
Working pressure (bar)	6
Tank material	Polyethylene
Pump	Brass Ø52 mm
Tank capacity lt	12 - 15
Tube length mt.	1,20
Filling entrance diameter mm	115
Nozzle	Mod. Get 928
Net weight kg	3,60
Package dimensions cm	45x15x58 (12 Lt) – 45x19x58 (15 Lt)



Davide e Luigi Volpi S.p.A.
Via San Rocco, 10
46040 CASALROMANO MN -ITALIA

COMPANY WITH QUALITY SYSTEM
MANAGEMENT CERTIFIED BY ICIM
= ISO 9001 =

Sprayer performances:

PRESSURE BAR	FLOW LT/MIN	NOZZLE GET 928 (HOLE 1,5)
1,7	0,77	60°
2,3	0,93	
2,9	1,10	
1,7	1,18	JET
2,3	1,39	
2,9	1,54	

IMPORTANT: CAREFULLY FOLLOW THE INDICATIONS FOR USE REPORTED INTO THE USER'S MANUAL.