

TECHNICAL DATASHEET
COMPRESSION SPRAYER 10Lt
COD. VT10E



The sprayer Volpitech VT10 with EPDM gaskets is designed for dispensing liquid solutions.

Sprayer	With safety valve
Lance lenght	40 cm
Max Pression	3 bar
Tank material	Polyethylene
Spring and Pin material	Inox aisi 304
Handle and Valve material	Inox aisi 302
O-rings material	EPDM
Tank capacity	10 Lt.
Filling diameter	60 mm
Nozzle material	Polypropylene
Net Weight kg	2,45
Package dimensions cm	22x22x65



Davide e Luigi Volpi S.p.A.
Via San Rocco, 10
46040 CASALROMANO MN –ITALIA

COMPANY WITH QUALITY SYSTEM
MANAGEMENT CERTIFIED BY ICIM
= ISO 9001 =

Spraying performance:

PRESSURE BAR	FLOW RATE LT/MIN	NOZZLE (HOLE 1,25)
1,0	0,22	60°
1,5	0,29	
2,0	0,37	
1,0	0,46	JET
1,5	0,61	
2,0	0,77	

Sprayer resistant to low solutions (up to about 20%) of alkaline components, detergents, industrial disinfectants, 10% ammonia, 5% bleach.

Sprayer not resistant to solvents, trichlorethylene, lacquers, petrol, diesel, hydraulic oils and fuels.

CLEANING: wash the tank after every use with clean water.

IMPORTANT: CAREFULLY FOLLOW THE INDICATIONS FOR USE REPORTED INTO THE USER'S MANUAL.