

TECHNICAL DATASHEET
KNAPSACK SPRAYER 12Lt
COD. VT12



Volpitech VT12 sprayer is designed for dispensing liquid solutions.



Davide e Luigi Volpi S.p.A.
Via San Rocco, 10
46040 CASALROMANO MN –ITALIA

COMPANY WITH QUALITY SYSTEM
MANAGEMENT CERTIFIED BY ICIM
= ISO 9001 =

Sprayer	With safety valve
Volpitech lance lenght cm	40
Pressure bar	6
Tank material	Polyethylene
Spring and pin material	Inox aisi 304
Handle and valve material	Inox aisi 302
O-ring material	FPM
Tank capacity Lt	12
Filling diameter mm	60
Nozzle material	polipropilene
Total Net Weight Kg	3,6
Package dimensions cm	45x15x58

Spraying Performance:

PRESSURE BAR	FLOW RATE LT/MIN	NOZZLE (HOLE 1,25)
1,0	0,22	60°
1,5	0,29	
2,0	0,37	
1,0	0,46	JET
1,5	0,61	
2,0	0,77	

Sprayer resistant to low solution (up to approximately 20%) of hydrochloric acid, to petrol, diesel oil, lime, detergents, herbicides, hydraulic and fuel oils, ethyl alcohol, white spirit.
Sprayer not resistant to acetone, paint thinner, solvents, trichloroethylene, lacquers.

CLEANING: wash the tank after every use with clean water.

IMPORTANT: CAREFULLY FOLLOW THE INDICATIONS FOR USE REPORTED INTO THE USER'S MANUAL.