

**TECHNICAL DATASHEET**  
**COMPRESSION SPRAYER**  
**COD. VT2**



VOLPITECH2 has been created to spray liquid solutions

Compression sprayer including	discharge valve and adjustable plastic nozzle
Max pression	2 bar
Head Material	Polypropylene
Tank material	High Density Polyethylene
Closing pin material	Special plastic
Pin and valve springs material	Stainless steel AISI 302
Nozzle material	Polypropylene
O-rings material	FPM
Tank capacity	2 Lt.
Filling diameter	60 mm.
Nozzle	Adjustable
Packaging dimensions cm	48x37x31
Packaging weight (10 pcs.) Kg	5,1



Daide e Luigi Volpi S.p.A.  
Via San Rocco, 10  
46040 CASALROMANO MN -ITALIA

COMPANY WITH QUALITY SYSTEM  
MANAGEMENT CERTIFIED BY ICIM  
= ISO 9001 =

Spraying performance:

PRESSURE BAR	FLOW RATE LT/MIN	NOZZLE (HOLE 1,25)
1,0 1,5 2,0	0,22 0,29 0,37	60°
1,0 1,5 2,0	0,46 0,61 0,77	JET

Sprayer resistant to medium solution (up to approximately 10%) of hydrochloric acid, to petrol, diesel oil, lime, detergents, herbicides, hydraulic and fuel oils, ethyl alcohol, white spirit.  
Sprayer not resistant to acetone, paint thinner, solvents, trichloroethylene, lacquers.

**CLEANING:** wash the tank after every use with clean water.