

TECHNICAL DATASHEET
COMPRESSION SPRAYER
COD.VT2E



VOLPITECH2 EPDM has been created to spray liquid solutions:

Compression sprayer	With discharge valve and adjustable plastic nozzle
Pression bar	2
Head material	Polypropylene
tank material	High Density Polyethylene
closing pin material	Special plastic
Pin and valve springs material	Stainless steel AISI 302
Nozzle material	Polypropylene
O-ring material	EPDM
Capacity of the tank Lt.	2
Filling diameter	60
Nozzle	Adjustable
Packaging dimensions cm	48x37x31
Weight of the carton box (10 pcs) kg	5,1



Davide e Luigi Volpi S.p.A.
 Via San Rocco, 10
 46040 CASALROMANO MN -ITALIA

COMPANY WITH QUALITY SYSTEM
MANAGEMENT CERTIFIED BY ICIM
= ISO 9001 =

Spraying performance:

PRESSURE BAR	FLOW RATE LT/MIN	NOZZLE (HOLE 1,25)
1,0 1,5 2,0	0,22 0,29 0,37	60°
1,0 1,5 2,0	0,46 0,61 0,77	JET

Sprayer resistant to law solutions (until around 20%) of alkaline components, detergents, industrial sanitizers.

Sprayer not resistant to acetone, solvents, varnish.

CLEANING: wash the tank after every use with clean water.