

TECHNICAL DATASHEET
ELECTRIC SPRAYER 7Lt
COD. VT7





Davide e Luigi Volpi S.p.A.
Via San Rocco, 10
46040 CASALROMANO MN –ITALIA

COMPANY WITH QUALITY SYSTEM
MANAGEMENT CERTIFIED BY ICIM
= ISO 9001 =

Tank capacity	7 Lt
Tank material	Polypropylene
Operating pressure	2,0 bar
Safety valve	Standard - 3 bar calibration
Pump	Diaphragm
Pressure switch	Standard for max pressure control
Rechargeable lithium battery	7,4 Vdc 2,6 Ah 19,24 Wh
Charging socket	Micro USB
Battery charge time	Up to 2,5 hours
Spraying Liters for each battery charge	Up to 45 liters
Extension	Nylon
Handles	Lever Jet
Nozzle	Polypropylene
Shoulder strap	Adjustable
Gaskets	FPM
Delivery hose length	1,2 mt
Filling mouth diameter	60 mm
Temperature min. / max.	5° C / 40° C
Overall dimensions cm	23 x 21,5 x 46
Total weight kg	1,35

Spraying performance:

PRESSURE BAR	FLOW RATE LT/MIN	NOZZLE (HOLE Ø 1,25 mm)
1,0	0,22	60° ROSE
1,5	0,29	
2,0	0,37	
1,0	0,46	JET
1,5	0,61	
2,0	0,77	

Sprayer resists to low solutions (up to about 20%) of hydrochloric acid, diesel oil, caustic soda, bleach, detergents, herbicides, degreasers, industrial disinfectants, descalers, hydraulic and fuel oils, ethyl alcohol.

CLEANING: wash the tank after every use with clean water.

IMPORTANT: CAREFULLY FOLLOW THE INDICATIONS FOR USE REPORTED INTO THE USER'S MANUAL.