

TECHNICAL DATASHEET
COMPRESSION SPRAYER 6Lt
COD. VT621E





Davide e Luigi Volpi S.p.A.
Via San Rocco, 10
46040 CASALROMANO MN –ITALIA

COMPANY WITH QUALITY SYSTEM
MANAGEMENT CERTIFIED BY ICIM
= ISO 9001 =

Compression sprayer	With pressure discharge valve
Volpitech Lance lenght (cm)	40
Working pressure (bar)	3
Tank material	Polypropylene
Pin material	Inox aisi 304
Spring (handle and valve) material	Inox aisi 302
O-ring material	EPDM
Tank capacity (lt)	6
Filling diameter (mm)	60
Nozzle Material	Polypropylene
Sprayer net weight (Kg)	1,35
Dimensions (cm)	23 x 21,5 x 46

Spraying performance:

PRESSURE BAR	FLOW RATE LT/MIN	NOZZLE (HOLE DIAM. 1,25)
1,0	0,22	60°
1,5	0,29	
2,0	0,37	
1,0	0,46	JET
1,5	0,61	
2,0	0,77	

Sprayer resistant to low solutions (up to about 20%) of alkaline components, detergents, industrial disinfectants, 10% ammonia, 5% bleach.

Sprayer not resistant to solvents, trichlorethylene, lacquers, petrol, diesel, hydraulic oils and fuels.

CLEANING: wash the tank after every use with clean water.

IMPORTANT: CAREFULLY FOLLOW THE INDICATIONS FOR USE REPORTED INTO THE USER'S MANUAL.