



In campo con te, dal 1879.

TECHNICAL DATASHEET PRE-COMPRESSION SPRAYER

"VOLPITECH 6"

COD. VT621



Volpitech



Compression sprayer	With pressure discharge valve, nylon fiberglass lance and lever handle. FPM gaskets.
Complete lance lenght in cm	65
Working pressure in bar	3
Tank material	Polypropylene
Pin material	PVDF
Material of handle and valve spring	Stainless steel
O-ring material	FPM
Tank capacity in Lt.	6
Filling diameter in cm	6,0
Nozzle	Adjustable and steerable in polypropylene
Net weight of the sprayer in Kg	1,35
Package dimensions in cm	23 x 21,5 x 46

Nozzle performance:

PRESSURE - BAR	FLOW RATE - LT/MIN	NOZZLES (HOLE D. 1,25)
1,0	0,22	60°
1,5	0,29	
2,0	0,37	
1,0	0,46	JET
1,5	0,61	
2,0	0,77	

Sprayer resistant to low solutions (up to about 20%) of alkaline components, detergents, industrial disinfectants, 10% ammonia, 5% bleach.

Sprayer not resistant to solvents, trichlorethylene, lacquers, petrol, diesel, hydraulic oils and fuels.

CLEANING: wash the tank after every use with clean water.

IMPORTANT: CAREFULLY FOLLOW THE INDICATIONS FOR USE REPORTED INTO THE USER'S MANUAL.