




In campo con te, dal 1879.

TECHNICAL DATASHEET PRE-COMPRESSION SPRAYER

"VOLPITECH 10E"

COD. VT10E



Volpitech



Davide e Luigi Volpi S.p.A.
Via San Rocco, 10
46040 CASALROMANO MN - ITALIA

Tel. +39 0376 76009
Fax +39 0376 76408
info@volpioriginale.it

REG. IMP. C.F. e P.IVA 00136560208
Cap. Soc. € 955.000,00 i.v.
R.E.A. 75331 MANTOVA

www.volpioriginale.it

Compression sprayer	With pressure discharge valve, nylon fiberglass lance and lever handle. EPDM gaskets.
Complete lance lenght in cm	65
Working pressure in bar	3
Tank material	Polyethylene
Pin material	PVDF
Material of handle and valve spring	Stainless steel
O-ring material	EPDM
Tank capacity in Lt.	10
Filling diameter in cm	6,0
Nozzle	Adjustable and steerable in polypropylene
Net weight of the sprayer in Kg	2,47
Package dimensions in cm	22 x 22 x 65

Nozzle performance:

PRESSURE - BAR	FLOW RATE - LT/MIN	NOZZLES (HOLE D. 1,25)
1,0	0,22	60°
1,5	0,29	
2,0	0,37	
1,0	0,46	JET
1,5	0,61	
2,0	0,77	

Sprayer resistant to low solutions (up to about 20%) of alkaline components, detergents, industrial disinfectants, 10% ammonia, 5% bleach.

Sprayer not resistant to solvents, trichlorethylene, lacquers, petrol, diesel, hydraulic oils and fuels

CLEANING: wash the tank after every use with clean water.

IMPORTANT: CAREFULLY FOLLOW THE INDICATIONS FOR USE REPORTED INTO THE USER'S MANUAL.