

TECHNICAL DATASHEET OLIVE HARVESTER

OLYTECH "LITHIUM PLUS 888Wh"

COD. 675L-675XL



Olytech LITHIUM PLUS 888Wh is the olive harvester featuring a patented horizontal alternating movement.

Tilting head design for optimal entry into plants, designed for quick tine replacement. Equipped with telescopic extension and ergonomic handle.

Olytech LITHIUM PLUS 888Wh operates with a high-performance 48 V electric motor, powered by a 44,4V 20Ah 888Wh lithium battery.

Three-speed settings adjustable directly on the handle (+ / -).

Available in 2 versions:

- **675L** extendable from 2100 mm to 3000 mm,
- **675XL** extendable from 2400 mm to 3600 mm,

Olytech LITHIUM PLUS 888Wh allows a productivity of 90/120 kg/hour.

OLYTECH 675L – 675XL	
TYPE OF MOVEMENT	2 TINE-HOLDER ARMS WITH HORIZONTAL ALTERNATING MOVEMENT - PATENTED -
ELEMENTS OF THE HEAD	4 + 4 CARBON FIBER TINES QUICK REPLACEMENT
ENGINE	ELECTRIC 48V cc HIGH PERFORMANCE AND LOW CONSUMPTION
BATTERY INCLUDED	BACKPACK LITHIUM BATTERY 44,4V - 20Ah - 888Wh
BATTERY LIFE	7 HOURS (depending on the mode of use)
ELECTRONIC CONTROL	MICROPROCESSOR WITH MOTHERBOARD INTEGRATED IN THE HANDLE
LENGHT	675L FROM 2100 mm TO 3000 mm 675XL FROM 2400 mm TO 3600 mm
TOTAL WEIGHT	675L = 2,1 Kg – 675XL = 2,5 Kg
PRODUCTIVITY	90÷120 kg/hour
SPEED	850 - 950- 1050 RPM
POWER CABLE	2,2 mt WITH CONNECTORS
HANDLE	ERGONOMIC WITH SWITCH AND ANTI-BENDING CABLE

IMPORTANT: FOLLOW STRICTLY THE INSTRUCTIONS RELATED TO THE USE OF THE PRODUCTS, GIVEN ON THE INSTRUCTION MANUAL.