

TECHNICAL DATASHEET OLIVE HARVESTER

OLYTECH "SUPER POWER"

COD. "555L" "555XL"



SUPER POWER features a microprocessor for controlling the engine power, directly positioned on the power supply. Using the buttons, the operator can select two different working speeds: 950 or 1050 cycles per minute.

The tilted head allows the operator to carry out all types of movement: combing (from top to bottom) or beating (insertion in and out of the branches, in all positions).

Equipped with telescopic extension and ergonomic handle- patented.

Olytech SUPER POWER features a 48V electric motor.

Available in 2 versions:

- **555L** extensible from 2100 mm to 3000 mm,
- **555XL** extensible from 2400 mm to 3600 mm,

Olytech SUPER POWER allows a productivity of 90/120 Kg/hour.

| OLYTECH 555L – 555XL | |
|-----------------------------|--|
| TYPE OF MOVEMENT | 2 TINE-HOLDER ARMS WITH HORIZONTAL ALTERNATING MOVEMENT - PATENTED - |
| ELEMENTS OF THE HEAD | 4 + 4 CARBON FIBER TINES QUICK REPLACEMENT |
| ENGINE | ELECTRIC 48V cc HIGH PERFORMANCE AND LOW CONSUMPTION |
| POWER SUPPLY | ELECTRIC 12V / 24V |
| RECOMMENDED BATTERY | 12 V cc – 70-80 Ah |
| ELECTRONIC CONTROL | MICROPROCESSOR WITH STANDARD POWER SUPPLY |
| SPEED | STANDARD DOUBLE SPEED |
| LENGHT | 555L FROM 2100 mm TO 3000 mm 555XL FROM 2400 mm TO 3600 mm |
| TOTAL WEIGHT | 555L = 2,5 Kg – 555XL = 2,8 Kg |
| PRODUCTIVITY | 90÷120 kg/hour |
| SPEED | 950- 1050 RPM |
| POWER CABLE | 15 m WITH CLAMPS AND CONNECTORS |
| HANDLE | ERGONOMIC WITH SWITCH AND ANTI-BENDING CABLE |

**IMPORTANT: FOLLOW STRICTLY THE INSTRUCTIONS RELATED TO THE USE OF THE PRODUCTS,
GIVEN ON THE INSTRUCTION MANUAL.**